

Hydroblaster Pressure Washer

10/3000 EHOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 10/3000EHOV high-pressure hot water systems provide flow of 10GPM with variable pressure up to 3000PSI. All EHOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high-efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

- Full Equipment Covers
- Belt Driven Pump
- Schedule 80 Coil Warranty
- Automatic Ignition
- 6 Gallon Fuel Oil Tank
- Soap/Chemical Injection
- Variable Pressure Trigger Wand
- 15-Degree Nozzle

Optional Features

- 50-Hz Motor
- Stainless Steel Covers
- Electrical Disconnect
- Power Vent With Controller
- Automatic Shut Down Timer
- [Remote Station Operation](#)
- Trigger Activated Start
- Steam Combo
- Pressure Gauge
- Precision Thermal Management (PTM)
- Hour Meter
- [High Pressure Soap/Chemical Injection](#)
- Select 50', 75' or 100' High Pressure Discharge Hose
- Hose Reel
- Float Tank
- Nozzle Sets
- [Turbo Nozzle](#)



Pricing

For complete pricing details,
Submit a quote online below.

[Get a Quote](#)



Hydroblaster Pressure Washer

10/3000 EHOV - Electric Motor, Hot Water Pressure Washer

Specifications

| | |
|------------------------------|--|
| Volume - GPM (LPM) | 10 (37.8) |
| Pressure - PSI (BAR) | 3000 (207) |
| BTU Minimum Supply | 900,000 |
| Exhaust Diameter - Inch (mm) | 12" (304.8) |
| Electric Motor - HP (KW) | 20 (14.9) |
| Dimensions, Inches (cm) | 58" (147.3) L x 40" (101.6) W x 69" (175.3)H |
| Weight, Lbs (kg) | 1685 (764) |

| | Standard | |
|---------------------|----------|---------|
| Volts (60Hz) | 230V-3P | 460V-3P |
| Amps (60Hz) | 53 | 27 |

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)

