



HN30004E2G-PP 4GPM@3000PSI

Standard Accessories

- Gun/wand assembly
- 50' high pressure hose
- Full pressure chemical injection, precision stainless steel metering valve
- 3 color-coded QC spray nozzles (15", 25", 40")

Available Options

- Machine mount hose reel (AR425, AR151)
- Draft diverter (BGD10)
- Downstream soap injection (AC340)
- Wind-up timer remote (AEN80)
- Hour meter (AM603)
- Full function, wall mount, remote with hour meter (-R)
- Liquid Propane conversion (-LP)
- Diesel fired conversion, includes 18g fuel tank (-D)

Standard Features

- Clean and efficient heating system
- NEMA4 water tight electrical box
- By-Pass-Cool system protects pump from overheating if left on after use
- 24 volt automatic ignition system on low emission natural gas burner
- Durable frame construction
- Best in class accessibility
- Dual rated for 208v or 230v - 1ph, 20 amp
- V-Belt drive with EZ align pump rail
- General Pump

More Standard Features

- Heavy duty industrial motor with standard thermal overload protection
- Adjustable temperature up to 250°F
- Burst disc technology for operator safety
- Rustproof float tank to regulate incoming water ensuring consistent system performance
- Remote ready: Choose an on/off timer remote option or a full function remote option for complete control from the wash site