

## Ausführungen | Versions ST-1500

Bezeichnung Description	E	A	Farben / Colours			Artikel-Nr. Item-No.
	Eingang Inlet	Ausgang Outlet	Gehäuse Housing	Hebel Trigger	Klinke Lock	
ST-1500	G3/8 IG G3/8 female	G1/4 IG G1/4 female	schwarz black	schwarz black	rot red	20 1500 500
ST-1500 NPT Weep	3/8" NPT IG 3/8" NPT female	1/4" NPT IG 1/4" NPT female	schwarz black	blau blue	gelb yellow	20 1500 515
ST-1500 M22x1,5	M22x1,5 AG M22x1,5 male	M22x1,5 AG M22x1,5 male	schwarz black	schwarz black	rot red	20 1500 545
ST-1500 M22x1,5	M22x1,5 AG M22x1,5 male	G1/4 IG G1/4 female	schwarz black	schwarz black	rot red	20 1500 550
ST-1500 Drehgelenk ST-1500 Swivel	G3/8 IG Drehglk. G3/8 female Swiv.	G1/4 IG G1/4 female	schwarz black	schwarz black	rot red	20 1500 560
ST-1500 Frostschutz ST-1500 Freeze protect.	G3/8 IG G3/8 female	G1/4 IG G1/4 female	schwarz black	blau blue	rot red	20 1500 580
ST-1500 Frostschutz ST-1500 Freeze protect.	G3/8 IG Drehglk. G3/8 female Swiv.	G1/4 IG G1/4 female	schwarz black	blau blue	rot red	20 1500 581
ST-1500 Weep	G3/8 IG G3/8 female	G1/4 IG G1/4 female	schwarz black	blau blue	gelb yellow	20 1500 620
ST-1500 Kupplung ST-1500 Coupler	G3/8 IG G3/8 female	Kupplung Coupler	schwarz black	schwarz black	rot red	20 1500 660
ST-1500 Drehglk. Kuppl. ST-1500 Swivel Coupler	G3/8 IG Drehglk. G3/8 female Swiv.	Kupplung Coupler	schwarz black	schwarz black	rot red	20 1500 670

## Technische Daten | Specification

Druck   Pressure	275 Bar		4000 psi
Temperatur   Temperature	150° C		300° F
Durchfluss   Flow rate	45 l/min		12 US gal/min
Druckverlust Pressure drop	9 bar 130 psi	(bei 30 l/min) (at 8 US gal/min)	
Öffnungskraft, Haltekraft   Triggering force, hold. force			
100 bar   1450 psi:	62 N,		39 N
200 bar   2900 psi:	117 N,		43 N
275 bar   4000 psi:	184 N,		53 N
Gewicht   Weight	0,45 kg		
	0,5 kg	mit Swivel	
Material   Material	Messing   Brass		
	Edelstahl   Stainless steel		

