

Hydroblaster Pressure Washer

5/1500 EHGV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 5/1500EHGV high-pressure hot water systems provide flow of 5GPM with variable pressure up to 1500PSI. All EHGV systems can be configured for natural gas or propane heating operation. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHGV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

- Full Equipment Covers
- Draft Diverter
- Belt Driven Pump
- Schedule 80 Coil Warranty
- Automatic Ignition
- Soap/Chemical Injection
- Variable Pressure Trigger Wand
- 15-Degree Nozzle

Optional Features

- Fuel - Natural Gas or LP Gas
- 50-Hz Motor
- Stainless Steel Covers
- Electrical Disconnect
- Power Vent With Controller
- Automatic Shut Down Timer
- [Remote Station Operation](#)
- Trigger Activated Start
- Steam Combo
- Pressure Gauge
- Precision Thermal Management (PTM)
- Hour Meter
- [High Pressure Soap/Chemical Injection](#)
- Select 50', 75' or 100' High Pressure Discharge Hose
- Hose Reel
- Float Tank
- Nozzle Sets
- [Turbo Nozzle](#)



Pricing

For complete pricing details,
Submit a quote online below.

[Get a Quote](#)



Hydroblaster Pressure Washer

5/1500 EHGV - Electric Motor, Hot Water Pressure Washer

Specifications

Volume - GPM (LPM)	5 (18.9)
Pressure - PSI (BAR)	1500 (103)
BTU Minimum Supply	400,000
Exhaust Diameter - Inch (mm)	10" (254)
Electric Motor - HP (KW)	5 (3.73)
Dimensions, Inches (cm)	45" (114.3) L X 33" (83.8) W X 54" (137.2) H
Weight, Lbs (kg)	688 (312)

	Standard		
Volts (60Hz)	230V-1P	230V-3P	460V-3P
Amps (60Hz)	23	14	7

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)

