

**Pressure-Pro™**

**HOT SHOT SERIES**



**4012-10C**

**4GPM @ 4000PSI**



**66DX40 Direct Drive Pump**

**POWERED by HONDA GX390 Engine**

### **STANDARD ACCESSORIES**

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- Maxi-Flo 20% chemical injector assembly with quick connects
- 4 color-coded QC spray nozzles

### **AVAILABLE OPTIONS**

- ATK005 Adjustable Thermostat
- BRK100 Brake Kit
- HRK415 Hose Reel Kit, 150' x 3/8" max. w/no add'l hose

Gasoline Honda and Diesel powered models include electric start, and battery with marine battery box.

### **STANDARD FEATURES**

- Rugged powder coated steel roll cage frame with lifting hook, 13" flat free tires, Dim. 30" x 47" x 48"
- Super efficient schedule 80 coil with one-piece molded insulation combustion chamber
- Stainless steel coil wrap
- 8 gallon poly diesel fuel tank with fuel filter
- Commercial/Industrial grade engines
- Reliable Beckett burners
- High limit over temp protection
- Safety pressure relief valve
- Thermo-sensor (prevents overheating in bypass mode)