

Ausführungen | Versions ST-2700

Bezeichnung Description	E	A	Farben / Colours			Artikel-Nr. Item-No.
	Eingang Inlet	Ausgang Outlet	Gehäuse Housing	Hebel Trigger	Klinke Lock	
ST-2700 blau ST-2700 blue	G3/8 IG G3/8 female	G1/4 IG G1/4 female	blau blue	blau blue	rot red	20 2700 500
ST-2700 schwarz ST-2700 black	G3/8 IG G3/8 female	G1/4 IG G1/4 female	schwarz black	schwarz black	rot red	20 2700 550
ST-2700 Kupplung ST-2700 Coupling	G3/8 IG G3/8 female	Kupplung Coupling	schwarz black	schwarz black	rot red	20 2700 560
ST-2700 NPT	3/8" NPT IG 3/8" NPT female	1/4" NPT IG 1/4" NPT female	schwarz black	schwarz black	rot red	20 2700 600

Technische Daten | Specification

Druck Pressure	310 bar		4500 psi
Temperatur Temperature	150° C		300° F
Durchfluss Flow rate	45 l/min		12 US gal/min
Druckverlust	7,5 bar	(bei 30 l/min)	
Pressure drop	108 psi	(at 8 US gal/min)	
Öffnungskraft, Haltekraft Triggering force, hold. force			
100 bar 1450 psi:	31 N,		10 N
200 bar 2900 psi:	61 N		15 N
310 bar 4500 psi:	92 N,		20 N
Gewicht Weight	0,60 kg		
	0,65 kg		mit Swivel

