

Safety Data Sheet Elephant Snot Graffiti Remover Revision Date: 1/12/18

Prepared according to Global Harmonized System (GHS) standards

**SECTION 1** 

**CHEMICAL PRODUCT IDENTIFICATION** 

Lubrication Technologies, Inc. 900 Mendelssohn Avenue North Golden Valley, MN 55427-4309 Tel: 763-545-0707

Product Trade Name:

# Elephant Snot Graffiti Remover

CAS Number: Synonyms/Other: Recommended Use: Restrictions on Use: Created Date: Preparation/Revision Date: Emergency Phone Number: SDS CODE:

N/A Graffiti remover Not determined 4/24/2015 1/12/2018 1-800-424-9300 (CHEMTREC) 13309

#### **SECTION 2**

#### HAZARD IDENTIFICATION

Appearance: Odor: Classification:	Grey gelatin Slight chemical odor Skin corrosion / irritation category 1 Sensitization - skin category 1 Eye damage / irritation category 1 Acute Toxicity - oral category 4 Acute Toxicity - dermal category 4 Acute Toxicity - inhale category 4
Target Organs:	Skin, Eyes, Lungs
Pictogram(s):	
Signal Word:	DANGER
Hazard Statement:	H302 - Harmful if swallowed H312 - Harmful in contact with skin H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction H318 - Causes serious eye damage H332 - Harmful if inhaled
Other Hazards: Prevention:	Not determined. P260 - Do not breathe dust/fume/gas/mist/vapours/spray P264 - Wash hands thoroughly after handling P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area P272 - Contaminated work clothing should not be allowed out of the workplace P280 - Wear protective gloves/protective clothing/eye protection/face protection P285 - In case of inadequate ventilation wear respiratory protection



Safety Data Sheet Elephant Snot Graffiti Remover Revision Date: 1/12/18

Response:	<ul> <li>P310 - Immediately call a POISON CENTER or doctor/physician</li> <li>P321 - Specific treatment (see Section 4)</li> <li>P363 - Wash contaminated clothing before reuse</li> <li>P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell</li> <li>P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting</li> <li>P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower</li> <li>P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing</li> <li>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.</li> <li>Remove contact lenses if present and easy to do – continue rinsing</li> <li>P333+P313 - If skin irritation or a rash occurs: Get medical advice/attention</li> </ul>
Storage Procedures: Disposal:	P405 - Store locked up P501 - Dispose of contents and container in accordance with federal, state, and local regulations
Other:	See section 11 for complete health hazard information.

**SECTION 3** 

### COMPOSITION OF INGREDIENTS

Component	CAS Number	Percentage (by weight)
Benzyl Alcohol	100-51-6	60-80%
Proprietary Blend	Trade Secret	Trade Secret

Trade Secret Information: Specific chemical(s) and/or percentage of composition has been withheld as a trade secret.

SECTION 4	FIRST AID MEASURES
Eye Contact:	Avoid direct contact. Wear chemical protective gloves, if necessary. Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately call a doctor.
Skin Contact:	Avoid direct contact. Wear chemical protective clothing, if necessary. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash skin with lukewarm, gently flowing water and mild soap until product is removed. Immediately call a doctor. If breathing has stopped, trained personnel should begin rescue breathing or, if the heart has stopped, immediately start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). Avoid mouth-to-mouth contact by using a barrier device. If skin irritation or rash occurs: Get medical advice/attention. Discard contaminated clothing.
Inhalation:	Take precautions to ensure your own safety (e.g. wear appropriate protective equipment). Remove source of exposure or move person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
Ingestion:	Rinse mouth. Do NOT induce vomiting. Immediately call a doctor. If vomiting occurs naturally, lie on your side, in the recovery position.
Other:	No additional information



#### **SECTION 5**

#### FIRE FIGHTING MEASURES

Flash Point: Flammable limits: Extinguishing media: Special firefighting procedures	<ul> <li>220°C by Cleveland Open Cup Tester.</li> <li>Not applicable.</li> <li>Seneral directions - product will not burn without driving water from material first.</li> <li>Evacuate area and fight fire from a safe distance. If leak or spill has not ignited, ventilate area and use water spray to disperse gas or vapor and to protect personnel attempting to stop a leak. Use water spray to cool adjacent structures and to protect personnel. Shut off source of flow if possible (safely). Stay away from storage tank ends. Withdraw immediately in case of rising sound from venting safety device or any discoloration of storage tank due to fire. Fire fighters must wear MSHA/NIOSH approved positive pressure breathing apparatus (SCBA) with full face mask and full protective equipment.</li> </ul>
Unusual fire & explosion hazards: Byproducts of combustion: Autoignition temperature: Explosion data: Other:	<ul> <li>High temperatures may create heavy flammable vapors that may settle along ground level and low spots to create an invisible fire hazard.</li> <li>Fires involving this product may release oxides of carbon, nitrogen and sulfur; reactive hydrocarbons and irritating vapors.</li> <li>Not determined.</li> <li>Not determined. Care should always be exercised in dust/mist areas.</li> <li>Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.</li> </ul>

#### SECTION 6

#### ACCIDENTAL RELEASE MEASURES

Spill control procedures (land): Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment, flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective equipment should contain spill immediately with inert materials (sand, earth, chemical spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner that will prevent material from entering sewers and waterways. Large spill, once contained, may be picked up using explosion proof, non-sparking vacuum pumps, shovels, or buckets, and disposed of in suitable containers for disposal. If a large spill occurs notify appropriate authorities. In case of road spill or accident contact Chem-Trec (800-424-9300).

Spill control procedures<br/>(water):Try to contain large spills with floating booms to prevent spill from spreading. Remove<br/>from surface by skimming or with suitable adsorbents. If a large spill occurs notify<br/>appropriate authorities (normally the National Response Center or Coast Guard at 800-<br/>424-8802).

Waste disposal method: Do not empty into drains. All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.

Other: CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will be regulated.

#### SECTION 7

#### HANDLING AND STORAGE

Handling procedures:Keep containers closed when not in use. Do not transfer to unmarked containers. Empty<br/>containers retain product residue which may exhibit hazards of material, therefore do not<br/>pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation<br/>centers for proper cleaning and reuse.<br/>Handling temperatures should not exceed 60°C (140°F) to minimize danger of burns.<br/>Open containers carefully in a well ventilated area or use appropriate respiratory<br/>protection. Wash thoroughly after handling.



Safety Data Sheet Elephant Snot Graffiti Remover Revision Date: 1/12/18

Storage procedures:

Store containers away from heat, sparks, open flame, or oxidizing materials. Extended storage at excessive temperatures may produce odorous and toxic fumes from product decomposition. No additional information.

Additional information:

#### **SECTION 8**

#### **EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### Exposure limits/standards for materials that can be formed when handling this product:

Component	CAS Number	OSHA PEL	ACGIH TLV
Benzyl Alcohol	100-51-6	ND	ND
Proprietary Blend	Trade Secret	ND	ND

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.


No biological limits allocated.

Personal protection:	Applicable mainly to persons in repeated contact situations such as packaging of product, service/maintenance, and cleanup/spill control personnel.
Respiratory protection:	None required if ventilation is adequate. Otherwise a respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. Where misting may occur, wear an MSHA/NIOSH approved (or equivalent) half-mask form dust/mist air purifying respirator.
Eye protection:	Eye protection is strongly recommended. Wear safety glasses with side shields or vented/splash proof goggles (ANSI Z87.1 or approved equivalent).
Hand protection:	Impervious, chemically resistant gloves such as neoprene or nitrile rubber to avoid skin sensitization and absorption.
Other protection:	Use of an apron and overboots of chemically impervious materials such as neoprene or nitrile rubber is recommended based on level of activity and exposure. If handling hot material use insulated protective equipment. Launder soiled clothes. Properly dispose of contaminated leather articles and other materials which cannot be decontaminated.
Local control measures:	Use adequate ventilation when working with material in an enclosed area. Mechanical methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure. Eyewash stations and showers should be available in areas where this material is used and stored.
Other:	Consumption of food and drink should be avoided in work areas where product is present. Always wash hands and face with soap and water before eating, drinking or smoking.

#### **SECTION 9**

#### PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Grey gelatin
Odor:	Slight chemical odor
Odor threshold:	Not determined.
pH:	12.5-13.5
Melting/Freezing point:	Not determined.
Initial boiling point:	205°C.
Boiling range:	Not determined.
Flash point:	220°C.
Evaporation rate:	Not determined.
Flammability:	Non-flammable
Upper flammable limit:	Non-flammable





Lower flammable limit:	Non-flammable
Vapor pressure:	Not determined.
Vapor density:	Not determined.
Relative density:	Not determined.
Solubility:	Miscible in water, negligible in most petroleum solvents.
Partition Coefficient:	Not determined.
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Viscosity:	Not determined.
Other	Not applicable.

#### **SECTION 10**

**SECTION 11** 

#### STABILITY AND REACTIVITY

Reactivity	
Chemical stability:	Material is chemically stable at room temperatures and pressure.
Hazardous polymerization:	Will not occur.
Conditions to avoid:	Avoid high temperatures and product contamination.
Incompatibility with other materials:	Avoid contact with acids and strong oxidizing materials.
Decomposition products:	Smoke, carbon monoxide, carbon dioxide, and other aldehydes of incomplete combustion. Oxides of carbon, nitrogen, and sulfur; reactive hydrocarbons and irritating vapors.
Other:	Not applicable.

#### Other:

#### **TOXICOLOGICAL INFORMATION**

#### Acute toxicity (LD50) \*See note at the bottom of the section

	s at the bottom of the section
Oral:	300 - 2000 mg/kg
Dermal:	1000 - 2000 mg/kg
Inhalation:	10.0 - 20.0 mg/l
Skin irritation:	Causes severe skin burns and eye damage
Eye irritation:	Causes serious eye damage
Dermal sensitization:	May cause an allergic skin reaction
Respiratory sensitization:	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Aspiration Hazard:	Not applicable
Chronic Toxicity	
Mutagenicity:	Not suspected of causing genetic defects
Carcinogenicity:	Not suspected of causing cancer.
Reproductive toxicity:	Not expected to have adverse effects on reproduction.
STOT-single exposure:	Not expected to have adverse effects.
STOT-repeated exposure:	Not expected to have long term adverse effects.
Other:	*All data in this section is based off calculations from Part 3 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

#### **SECTION 12**

#### **ECOLOGICAL INFORMATION**

Environmental toxicity	
Fish:	> 100 mg/l.
Invertebrates:	> 100 mg/l.
Aquatic plants:	> 100 mg/l.
Microorganism:	> 100 mg/l.
Persistence/Degradability:	This product is not expected to be readily biodegradable.



Bioaccumulation: Mobility in soil: Other:

## Not determined.

Not determined.

All classifications are based on calculations in Part 4 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

#### SECTION 13

#### **DISPOSAL CONSIDERATIONS**

Waste disposal:

Other

This product unadulterated by other materials can be classified as a non-hazardous waste. Depending on use, used product may be regulated. Dispose of in a licensed facility. Do not discharge product in to sewer system. Dispose of containers by crushing or puncturing, so as to prevent unauthorized use of used containers. Waste management should be in full compliance with federal, state, and local laws.

The transportation, storage, treatment and disposal of RCRA waste material must be conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.

#### **SECTION 14**

**SECTION 15** 

#### **TRANSPORT INFORMATION**

Land Transport (DOT): Proper Shipping Name: Land Transport (TDG): Proper Shipping Name: Sea Transport (IMDG): Proper Shipping Name: Air Transport (IATA): Proper Shipping Name: Other: UN3266 Corrosive liquid, basic, inorganic, 8, PG III Not regulated for land transport. Not applicable. Not regulated for sea transport. Not applicable. Not regulated for air transport. Not applicable. Not applicable.

#### **REGULATORY INFORMATION**

Federal Regulation			
Clean water act/oil:	No components of this product are listed.		
TSCA:	All components of this material are listed in the U.S. TSCA Inventory.		
Other TSCA:	Not applicable.		
SARA title III:	Section 302/304 extremely hazardous substances:		
	None.		
Section 311, 312 hazard categorization:			
	Acute (immediate health effects):	YES	
	Chronic (delayed health effects):	YES	
	Fire (hazard):	NO	
	Reactivity (hazard):	NO	
	Pressure (sudden release hazard):	NO	
	Section 313 toxic chemicals:		
	No components present are at or greater than the de minimis (minimum reportable) concentration requirements for reporting.		
CERCLA:	For stationary/moving sources – reportable quant petroleum exclusion.	ity (due to): Not hazardous due to the	



State Regulations	
Right-to-know	Not determined.
California Proposition 65	This product can expose you to chemical(s) which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
Other:	A release of this product, as supplied, is exempt from reporting under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA). However, releases may be reportable to the Nation Response Center under the Clean Water Act, 33 U.S.C.

civil and criminal penalties.

Recommend contacting the local authorities in the event of any type of spill to determine local reporting requirements and also to aid in the cleanup.

1321(b)(3) and (5) - see head of Section 15. Failure to report may result in substantial

SECTION 16	OTHER	OTHER INFORMATION		
	NFPA 704	NPCA-HMIS	KEY	
HEALTH:	2	2	0 = Minimal	
FIRE:	1	1	1 = Slight	
REACTIVITY:	0	0	2 = Moderate	
SPECIFIC HAZARD:	None	N/A	3 = Serious	
PROTECTION INDEX:	N/A	В	4 = Severe	
Version:	III			

INFORMATION PROVIDED IN THIS SDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF THE AUTHORS' KNOWLEDGE. HOWEVER, THE AUTHOR'S MAKE NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF THE INFORMATION HEREIN PRESENTED. THE AUTHORS ASSUME NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.

Revisions / Comments:	None. 04/25/15
	Document review. 05/05/17
	Document review. 01/12/18

Internal use only:

WB5-SD