

Hydroblaster Pressure Washer 5/1500 EHOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 5/1500EHOV high-pressure hot water systems provide flow of 5GPM with variable pressure up to 1500PSI. All EHOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high-efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

Full Equipment Covers
Belt Driven Pump
Schedule 80 Coil Warranty
Automatic Ignition
6 Gallon Fuel Oil Tank
Soap/Chemical Injection
Variable Pressure Trigger Wand
15-Degree Nozzle

Optional Features

50-Hz Motor Stainless Steel Covers Electrical Disconnect Power Vent With Controller Automatic Shut Down Timer

Remote Station Operation
Trigger Activated Start
Steam Combo
Pressure Gauge
Precision Thermal Management (PTM)
Hour Meter
High Pressure Soap/Chemical Injection

Select 50', 75' or 100' High Pressure Discharge Hose

Hose Reel Float Tank Nozzle Sets Turbo Nozzle



Pricing

For complete pricing details, Submit a quote online below.

Get a Quote







Hydroblaster Pressure Washer 5/1500 EHOV - Electric Motor, Hot Water Pressure Washer

Specifications

Volume - GPM (LPM) 5 (18.9)
Pressure - PSI (BAR) 1500 (103)
BTU Minimum Supply 440,000
Exhaust Diameter - Inch (mm) 10" (254)
Electric Motor - HP (KW) 5 (3.73)

Dimensions, Inches (cm) 45" (114.3) L X 33" (83.8) W X 54" (137.2) H

Weight, Lbs (kg) 688 (312)

Standard

Volts (60Hz)	230V-1P	230V-3P	460V-3P	
Amps (60Hz)	23	14	7	

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



