



Hydroblaster Pressure Washer 5/2000 EHGV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 5/2000EHGV high-pressure hot water systems provide flow of 5GPM with variable pressure up to 2000PSI. All EHGV systems can be configured for natural gas or propane heating operation. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHGV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

Full Equipment Covers Draft Diverter Belt Driven Pump Schedule 80 Coil Warranty Automatic Ignition Soap/Chemical Injection Variable Pressure Trigger Wand 15-Degree Nozzle

Optional Features

Fuel - Natural Gas or LP Gas 50-Hz Motor Stainless Steel Covers Electrical Disconnect Power Vent With Controller Automatic Shut Down Timer Remote Station Operation

Trigger Activated Start Steam Combo Pressure Gauge Precision Thermal Management (PTM) Hour Meter High Pressure Soap/Chemical Injection Select 50', 75' or 100' High Pressure Discharge Hose Hose Reel Float Tank Nozzle Sets Turbo Nozzle



Pricing

For complete pricing details, Submit a quote online below.





Hydro Engineering, Inc. | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181

CENTER DUS CETERE AVAILABLE

Subject to change without notice Copyright Hydro Engineering, Inc. 2019



Hydroblaster Pressure Washer 5/2000 EHGV - Electric Motor, Hot Water Pressure Washer

Specifications

 Volume - GPM (LPM)
 5 (18.9)

 Pressure - PSI (BAR)
 2000 (138)

 BTU Minimum Supply
 400,000

 Exhaust Diameter - Inch (mm)
 10" (254)

 Electric Motor - HP (KW)
 7.5 (5.59)

 Dimensions, Inches (cm)
 45" (114.3) L X 33" (83.8) W X 54" (137.2) H

 Weight, Lbs (kg)
 710 (322)

Standard

Volts (60Hz)	230V-1p	230V-3P	460V-3P
Amps (60Hz)	33	22	11

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



Hydro Engineering, Inc. | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181