

Hydroblaster Pressure Washer

7/3000 EHOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 7/3000EHOV high-pressure hot water systems provide flow of 7GPM with variable pressure up to 3000PSI. All EHOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high-efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

- Full Equipment Covers
- Belt Driven Pump
- Schedule 80 Coil Warranty
- Automatic Ignition
- 6 Gallon Fuel Oil Tank
- Soap/Chemical Injection
- Variable Pressure Trigger Wand
- 15-Degree Nozzle

Optional Features

- 50-Hz Motor
- Stainless Steel Covers
- Electrical Disconnect
- Power Vent With Controller
- Automatic Shut Down Timer
- [Remote Station Operation](#)
- Trigger Activated Start
- Steam Combo
- Pressure Gauge
- Precision Thermal Management (PTM)
- Hour Meter
- [High Pressure Soap/Chemical Injection](#)
- Select 50', 75' or 100' High Pressure Discharge Hose
- Hose Reel
- Float Tank
- Nozzle Sets
- [Turbo Nozzle](#)



Pricing

For complete pricing details,
Submit a quote online below.

[Get a Quote](#)



Hydroblaster Pressure Washer

7/3000 EHOV - Electric Motor, Hot Water Pressure Washer

Specifications

Volume - GPM (LPM)	7 (26.5)
Pressure - PSI (BAR)	3000 (207)
BTU Minimum Supply	630,000
Exhaust Diameter - Inch (mm)	12" (304.8)
Electric Motor - HP (KW)	15 (11.19)
Dimensions, Inches (cm)	58" (147.3) L x 40" (101.6) W x 69" (175.3)H
Weight, Lbs (kg)	1095 (497)

	Standard	
Volts (60Hz)	230V-3P	460V-3P
Amps (60Hz)	36	18

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)

