

MANHOLE CLEANER

- ✓ With protection plate
- ✓ Optimal cleaning of vertical main
- ✓ Easy to use










TECHNICAL DATA

Pressure 2500 psi Temperature 250°F

Inlet 1/2" NPTF (TXS-2f) 1" NPTF (TXS-4f) Body stainless steel

für 2x 1/8" (TXS-2f) Nozzles* für 4x 1/8" (TXS-4f)

Throughput ph 3 - 12



TXS-2f with protective plate

Part No.	Ø	Weight		
81.037	12"	8.1 lbs		
81.047	16"	9.7 lbs		
81.057	20"	11.7 lbs		
81.067	24"	14.1 lbs		
81.087	32"	14.3 lbs		

* Nozzles not included.

TXS-4 f with double protective plate

Part No.	Ø	Weight		
81.923	20"	15.4 lbs		
81.928	16"	11.9 lbs		

Important: Do not use unprotected!

SILO CLEANER

- √ Adjusts to your application
- √ Equipped with stabilizer nozzles
- √ Completely maintenance-free



Mosmatic has a solution for cleaning Silo's and other large diameter verticle drops. The extendable arms with rollers help guide and maintain a close surface cleaning impact. Simply attach a suspension cable to the eyelets and use your winch to raise and lower the Silo Cleaner. Stabilizer nozzles increase the cleaning distance and impact and maintain a more concentrated spray pattern. Stainless steel construction and maintenance free design help to ensure long life and reliability.



Part No.	Length/Width	Height	Rotor Arm	Nozzles	Wheels	Weight
81.095	6'6"-11'6"	8"	82.9036	2x 0005 EG	4x ø4"	55 lbs

FEATURES

Variable Lengths & Foldable

The length of the rotating arm is easily adjusted from 80" to 140". Folding the Silo Cleaner allows for a tight fit into the Silo loading port.

TECHNICAL DATA

4000 psi Pressure 250°F Temperature Inlet 1/2" NPTF

