

Eastures & Renefits:

Vertical/Horizontal Application

## **ICT TECHNICALS**

## **Total Rust Eraser Concentrate**

Description: Item #850-1G

Applicable Surfaces

Pool Deck/Driveways

ICT Total Rust Eraser is a heavy-duty, highly concentrated rust and stain remover. Total Rust Eraser removes rust and other surface contaminates from a variety of surfaces including natural and artificial stone, brick, masonry, concrete, travertine, flamed granite, stucco, and other similar surfaces without etching, pitting, or damaging the surface or grout when properly applied. Total Rust Eraser will also treat iron, fertilizer and battery acid stains, and aid in efflorescence removal.

reatures & benefits.	Applicable 3ulfaces.
Heavy-duty	Brick Pavers/Clay Pavers
Concentrated	Concrete/Masonry/Stucco
Mild Odor	Natural Stone/Artificial Stone

CHARACTERISTICS AND TECHNICAL DATA	
<u>Liquid Properties</u>	Test Results
Appearance Wet	Orange Liquid
Odor	Mild
Weight Per Gallon	10.38
Coverage	100-125 sq. ft.
Shelf Life	2 years
Packaging	1 gal
Clean Up	Soap and Water

<u>Preparation:</u> Determine the <u>dilution ratio</u> prior to application. Always <u>test</u> a small area for compatibility prior to general use. Protect all surfaces you don't want **Total Rust Eraser** to come into contact with such as glass, plants, and metal surfaces. Pre-clean the surface with a pressure washer or surface cleaner. This will open up the pores of the concrete and allow **Total Rust Eraser** to penetrate deeper and remove more of the stain. Allow concrete to <u>completely dry</u> before applying **Total Rust Eraser**.

**Application:** Evenly apply **Total Rust Eraser** using a plastic tank sprayer. **Do not** use any metal containers or applicators. After applying evenly, let product sit on surface for 10-20 minutes depending on surface contaminates. For heavily soiled areas a stiff bristle broom may be used for agitation. **Rinse thoroughly**. **Note:** Deep seated rust stains may require additional applications/dwell time. During cleaning, overlap from section to section to ensure even cleaning. **Do not** apply to any polished, honed, or glazed surfaces. **Do not** use on Slate, Flagstone, or Bluestone.

<u>Dilution Ratios:</u> Total Rust Eraser is a highly concentrated material. Please read all safety precautions and dilution ratios prior to use. **Do not** apply at full strength. For heavy rust stains dilute 1:2 (1 part water to 2 parts **Total Rust Eraser**). For moderate rust stains, dilute 1:1 (1 part **Total Rust Eraser** to 1 part water). For light rust stains and painted surfaces dilute 2:1 (2 parts of water to 1 part **Total Rust Eraser**).

## **ICT Corporation**

2410 McJunkin Road \* Lakeland, FL 33803
(Nationwide): 888-296-5236 \* (Local): 863-665-8787 \*(Fax): 863-666-2768
(Email): info@innovativeconcrete.com
www.innovativeconcrete.com

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 2 years from the date of manufacturing when maintained in protected storage of 50°F to 90°F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond ICT's control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.

Rev 6/22/2021

## **Total Rust Eraser Concentrate**

Item # 850-1G

**Coverage:** Typical coverage will be 100-125 sq. ft. per gallon. Coverage rates will vary depending on application method, and the type of surface being cleaned.

Clean Up: Clean up all equipment with soap and water. Do not use a metal type sprayer or metal containers, plastic only.

Precautions: DANGER CORROSIVE LIQUID KEEP OUT OF REACH OF CHILDREN. For specific information, please refer to material safety data sheet. Use in well ventilated areas only. Do not breath mist or spray. Avoid exposure to mist by wearing a NOISH approved respirator during application and clean up. Follow respirator manufacturer's directions for use. Avoid contact with eyes and skin. Wear chemical resistant gloves, footwear, and goggles when using. Close container after each use. Wash thoroughly after handling.

First Aid: In case of contact with the eyes, flush with water for 15 minutes. Remove contact lenses if present and easy to do and continue flushing with water. Seek immediate medical attention. In case of contact with skin, wash with soap and water. Skin irritation and burns may not be immediately painful or visible. If irritation develops, seek immediate medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If breathing difficulty persists, get immediate medical attention. In case of ingestion, give person milk, chewable calcium carbonate tablets, or milk of magnesia. Do not induce vomiting. Never give anything by mouth to a person who is convulsing or unconscious. Seek immediate medical attention.

In Case of Spill: In the event of a spill, absorb with inert material and dispose of properly.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



















