

Ausführungen | Versions ST-2605

Bezeichnung Description	E	A	Farben / Colours			Artikel-Nr. Item-No.
	Eingang Inlet	Ausgang Outlet	Gehäuse Housing	Hebel Trigger	Klinke Lock	
ST-2605	G3/8 IG G3/8 female	G1/4 IG G1/4 female	schwarz black	schwarz black	rot red	20 2605 500
ST-2605 blau	G3/8 IG G3/8 female	G1/4 IG G1/4 female	blau blue	blau blue	rot red	20 2605 510
ST-2605 NPT	3/8" NPT IG 3/8" NPT female	1/4" NPT IG 1/4" NPT female	schwarz black	schwarz black	rot red	20 2605 600

Technische Daten | Specification

Druck Pressure	350 bar		5000 psi
Temperatur Temperature	150° C		300° F
Durchfluss Flow rate	45 l/min		12 US gal/min
Druckverlust Pressure drop	7,5 bar 108 psi	(bei 30 l/min at 8 US gal/min)	
Öffnungskraft, Haltekraft Triggering force, hold. force			
100 bar 1450 psi:	31 N,		10 N
200 bar 3600 psi:	61 N,		15 N
350 bar 7300 psi:	103 N,		22 N
Gewicht Weight	0,60 kg		

