

## Ausführungen | Versions ST-6

Bezeichnung Description	E	A	M	L	Schwimmer Float	Artikel-Nr. Item-No.
	Eingang Inlet	Ausgang Outlet	Manometer Gauge	PVC-Leitung PVC-cable		
Strömungswächter Flowswitch	G3/8 AG G3/8 male	G3/8 AG G3/8 male	G1/4 IG G1/4 female	1200 mm	12,3 mm	20 0006 500
Strömungswächter Flowswitch	G3/8 AG G3/8 male	G3/8 AG G3/8 male	G1/4 IG G1/4 female	1850 mm	12,3 mm	20 0006 501
Strömungswächter Flowswitch	G3/8 AG G3/8 male	G3/8 AG G3/8 male	G1/4 IG G1/4 female	1200 mm	12,1 mm	20 0006 510
Strömungswächter Flowswitch	G3/8 AG G3/8 male	G3/8 AG G3/8 male	G1/4 IG G1/4 female	1200 mm	12,5 mm	20 0006 530
Strömungswächter Flowswitch	G3/8 AG G3/8 male	G3/8 AG G3/8 male	G1/4 IG G1/4 female	ohne Schalter without switch	12,5 mm	20 0006 535
Strömungswächter Flowswitch	3/8"NPT AG 3/8"NPT male	3/8"NPT AG 3/8"NPT male	G1/4 IG G1/4 female	1200 mm	12,3 mm	20 0006 540

## Technische Daten | Specification

Druck   Pressure	310 bar	4500 psi
Durchfluss   Flow rate	30 l/min	8 US gal/min
Kontaktart   Contact	Schließer	Normally open
Spannung   Voltage	250 V AC / DC	
Strom   Current	3 A	
Leistung   rupturing capacity	120 VA	
Schaltzeit   Response time	35 ms	
Temperatur   Temperature	80 °C	176 °F
Gewicht   Weight	0,37 kg	

